



PROFESSIONAL
Water Sealant

Water Repellent Protection

Graffiti Protection* - Requires Two Coats

Substrate	Product Strength	Coverage rate Sq. ft. / gal	# coats
Block - Burnished	Extra (PWS-8)	100-125	1
Block - Fluted	Super (PWS-15)	60-125	1*
Block - Haydite (expanded shale)	Super (PWS-15)	50-80	1*
Block - Smooth (heavyweight)	Super (PWS-15)	100-125	1
Block - Split face	Super (PWS-15)	60-100	1*
Brick - hard fired vertical / horizontal	Regular (PWS-5)	125-150	1
Brick - Porous vertical	Extra (PWS-8)	100-150	1
Brick - Porous horizontal	Regular (PWS-5)	125-150	1
Concrete - poured, vertical / horizontal	Regular (PWS-5)	150-200	1
Concrete - Manufactured Stone	Regular (PWS-5)	125-150	1
Concrete - Pavers	Regular (PWS-5)	100-150	1
Concrete - Precast	Regular (PWS-5)	100-150	1
Granite** - porous	Regular (PWS-5)	100-150	1
Limestone	Extra (PWS-8)	100-150	1
Marble** - porous	Regular (PWS-5)	125-150	1
Sandstone	Extra (PWS-8)	100-150	1
Slate	Regular (PWS-5)	125-175	1
Stucco	Extra (PWS-8)	100-150	1
Wood - Cedar	Extra (PWS-8)	125-150	1
Wood - Treated	Regular (PWS-5)	150-175	1

Substrate	1st Coat	Coverage rate Sq. ft. / gal	2nd Coat	Coverage rate Sq. ft. / gal
Block - Burnished	Super (PWS-15)	100-125	Extra (PWS-8)	110-135
Block - Fluted	Super (PWS-15)	60-125	Super (PWS-15)	70-135
Block - Haydite (expanded shale)	Super (PWS-15)	50-80	Super (PWS-15)	60-90
Block - Smooth (heavyweight)	Super (PWS-15)	100-125	Super (PWS-15)	110-135
Block - Split face	Super (PWS-15)	60-100	Super (PWS-15)	70-110
Brick - hard fired vertical	Super (PWS-15)	125-150	Extra (PWS-8)	135-160
Brick - Porous vertical	Super (PWS-15)	100-150	Extra (PWS-8)	110-160
Concrete - poured, vertical	Super (PWS-15)	150-200	Extra (PWS-8)	160-210
Concrete - Manufactured Stone	Super (PWS-15)	125-150	Extra (PWS-8)	135-160
Concrete - Precast	Super (PWS-15)	100-150	Extra (PWS-8)	110-160
Granite** - porous	Super (PWS-15)	100-150	Extra (PWS-8)	110-160
Limestone	Super (PWS-15)	100-150	Extra (PWS-8)	110-160
Marble** - porous	Super (PWS-15)	125-150	Extra (PWS-8)	135-160
Sandstone	Super (PWS-15)	100-150	Extra (PWS-8)	110-160
Slate	Super (PWS-15)	125-175	Extra (PWS-8)	135-185
Stucco	Super (PWS-15)	100-150	Extra (PWS-8)	110-160

* Extremely porous block may require more than one coat. **Not recommended for polished surfaces.
Important tips or cautions:
 • Not for painted surfaces • Cover windows • Not for below-grade
 • Shut down air handling equipment and cover vents
 • Use Regular (PWS-5) and Extra (PWS-8) within 48 hours of opening. Use Super (PWS-15) same day.

* Not for use on horizontal surfaces **Not recommended for polished surfaces.

www.watersealant.com

PX Professional
PRODUCTS OF KANSAS, INC.
1-800-676-7346